

CRACK SEALER  
ESTIMATING CHART

APPROXIMATE USAGE

| APPROXIMATE USAGE |        | 1190**         | 3405**         | TruGuard**     |
|-------------------|--------|----------------|----------------|----------------|
| WIDTH*            | DEPTH* | LBS/<br>100 LF | LBS/<br>100 LF | GAL/<br>100 LF |
| 0.25              | 0.50   | 5.7            | 5.5            | 1.0            |
| 0.25              | 0.75   | 8.6            | 8.3            | 1.0            |
| 0.25              | 1.00   | 11.4           | 11.1           | 2.0            |
| 0.25              | 1.25   | 14.3           | 13.9           | 2.0            |
| 0.25              | 1.50   | 17.1           | 16.6           | 2.0            |
| 0.50              | 0.50   | 11.4           | 11.1           | 2.0            |
| 0.50              | 0.75   | 17.1           | 16.6           | 2.0            |
| 0.50              | 1.00   | 22.8           | 22.2           | 3.0            |
| 0.50              | 1.25   | 28.6           | 27.7           | 4.0            |
| 0.50              | 1.50   | 34.3           | 33.3           | 4.0            |
| 0.75              | 0.50   | 17.1           | 16.6           | 2.0            |
| 0.75              | 0.75   | 25.7           | 25.0           | 3.0            |
| 0.75              | 1.00   | 34.3           | 33.3           | 4.0            |
| 0.75              | 1.25   | 42.8           | 41.6           | 5.0            |
| 0.75              | 1.50   | 51.4           | 49.9           | 6.0            |
| 1.00              | 0.50   | 22.8           | 22.2           | 4.0            |
| 1.00              | 0.75   | 34.3           | 33.3           | 4.0            |
| 1.00              | 1.00   | 45.7           | 44.4           | 6.0            |
| 1.00              | 1.25   | 57.1           | 55.5           | 7.0            |
| 1.00              | 1.50   | 68.5           | 66.6           | 8.0            |
| 1.25              | 0.50   | 28.6           | 27.7           | 4.0            |
| 1.25              | 0.75   | 42.8           | 41.6           | 5.0            |
| 1.25              | 1.00   | 57.1           | 55.5           | 7.0            |
| 1.25              | 1.25   | 71.4           | 69.3           | 9.0            |
| 1.25              | 1.50   | 85.7           | 83.2           | 10.0           |

\*Width and Depth are shown in inches converted from fractions to 10ths.

\*\*1190, 3405 & TruGuard are products of Owens-Corning Trumbull Asphalt.

PACKAGING INFORMATION:

1190 - 60#'s/Carton, 50#'S/Pail, = Material Weight 8.8#'s/gallon  
 3405 - 60#'s/Cartan, 50#'s/Pail, = Material Weight 8.55#'s/gallon  
 2-30#"s/Carton (Twin-Pak)

TruGuard - 5 gls/Pail, 55 gls/Drum = Material Weight 8.3#'s/gallon