

A modified asphalt emulsion crackfiller designed for maintenance of asphalt and concrete pavements.

#### Features and Advantages

- " Ready to Use - Apply Kold Flo from the original container, with a pour pot, or a drum pump for faster application.
- " Minimal Preparation - No waiting for kettles to heat up. Crews are ready to go in minutes
- " Safe Application - No burns from hot applied material. Kold Flo is a ready-to-use, cold applied, pourable crackfiller.
- " Easy Application - No expensive equipment or experience is necessary.
- " Reduced Traffic Delay - When properly applied, Kold Flo can be driven over within 30 minutes without tracking.

#### Application Directions:

PREPARE: Blow or sweep cracks.

APPLY: Pour Kold Flo into the crack,  $\frac{3}{4}$  of the length. Allow a few minutes for Kold Flo to seep down into the crack.

COMPLETE: Using a "U" shaped Squeegee, push Kold Flo into the crack allowing the excess to fill the remaining  $\frac{1}{4}$  length of the crack. Add more Kold Flo if necessary. If cracks are deeper than 2", a second application may be required.

#### Additional Information:

- " KEEP FROM FREEZING! Kold Flo is an asphalt emulsion and must be store at temperatures above 35° F
- " Kold Flo should be applied when the ambient temperature is at least 50° F with no chance of rain expected for 8 hours. Extraneous water will destroy Kold Flo if it has not cured.
- " Kold Flo stored longer than three months may require stirring due to slight settling.
- " Clean tools with water immediately after use. If Kold Flo is cured, use only EPA approved solvents for cleaning. If Kold Flo dries on hands, use only EPA/OSHA approved hand cleaners.

#### Coverage:

##### For Cracks Measuring:

$\frac{1}{4}$ " (wide) x  $\frac{1}{4}$ " (deep) = 300 linear feet

$\frac{1}{2}$ " (wide) x  $\frac{1}{2}$ " (deep) = 75 linear feet

1" (wide) x 1" (deep) = 25 linear feet